



**Okuma**  
**Australia -**  
**Melbourne -**  
**Head Office**  
**3 Tampe Road**  
**Rowville Victoria**

**1 300 1**  
**OKUMA**

---

## Space Turn LB3000 EXIII

**Brand:** Okuma Australia  
**Product Code:** SPTLB#3000III  
**Availability:** In Stock  
**Weight:** 0.00kg  
**Dimensions:** 0.00cm x 0.00cm x 0.00cm

### Short Description

The LB 3000EX is built on Okuma's Thermo-Friendly Concept to ensure minimal thermal growth, and slanted box bed construction translates to unsurpassed quality and rigidity.

### Description

The LB 3000EX is built on Okuma's Thermo-Friendly Concept to ensure minimal thermal growth, and slanted box bed construction translates to unsurpassed quality and rigidity. Equipped with Okuma's high power, high torque PREX motor, this machine delivers high quality machining from heavy to high speed cutting. The operator-friendly Okuma OSP P500 control makes this machine not only easy to operate, but also to integrate with other peripheral equipment. A wide variety of bed lengths, bore sizes and options, including live tooling, sub-spindle and Y-axis, means there is a configuration to meet any shop's requirements.

### Specification

MODEL	UNIT	SPACE TURN LB3000 EXII
Max Work Length	mm	250 (no Tailstock), 500, 1000, 1300
Max Turning Dia	? mm	340-410
Spindle Speed	min <sup>-1</sup>	5000, 4200, 2800
Spindle Bore	mm	80, 91, 110
Turret		V12
Motor (VAC)	kW	22/15, 30/22
Floor Space	mm	2200x1734 / 3310x1895 / 4344x2162
Spec		L/M/W/MY/MW/MYW

L Turning only

M Multitasking specs (M-tool)

W Sub-spindle specs (W-axis)

MY Multitasking + Y-axis specs

MYW Multitasking + Y-axis + Sub-spindle specs (W-axis)

## Product Gallery

