



**Okuma  
Australia -  
Melbourne -  
Head Office  
3 Tampe Road  
Rowville Victoria**

**1 300 1  
OKUMA**

---

## VTM-2000YB



**Brand:** Okuma Australia

**Product Code:** vtm#2000

**Availability:** In Stock

**Weight:** 0.00kg

**Dimensions:** 0.00cm x 0.00cm x 0.00cm

### Short Description

VTM-2000YB five-axis combination lathe/machining center can perform turning, vertical, horizontal, and angled surface machining in one operation without reorienting the part in the chuck.

### Description

VTM-2000YB five-axis combination lathe/machining center can perform turning, vertical, horizontal, and angled surface machining in one operation without reorienting the part in the chuck. With operator control of spindle direction in relation to the surface of the work-piece, side cutting with straight end mills can be used to dramatically reduce cutting time compared with point cutting using ball end mills. Cutting efficiency can be increased significantly and the lifetime of the tooling can be extended, reducing overall production costs. The work spindle is supported at two locations by large diameter roller bearings offering precision control for the production of complex parts. The spindle's

geared head generates high torque capable of sustaining the heavy cutting necessary for parts such as large valve bodies.

### Specification

MODEL	UNIT	VTM-2000YB
Max Turning Diameter	? mm	2,000
Max Work Length	mm	1,400
Spindle Speed	min-1	5 to 500, 4 to 300
Turret		H1 - B-axis for ATC
Motor (VAC)	kW	30/22
Floor Space	mm	5512x5471, 5970x6973

### Product Gallery

