



**Okuma
Australia -
Melbourne -
Head Office
3 Tampe Road
Rowville Victoria**

**1 300 1
OKUMA**

SIMUL TURN LU3000EX



Brand: Okuma Australia
Product Code: STLU#3000
Availability: In Stock
Weight: 0.00kg
Dimensions: 0.00cm x 0.00cm x 0.00cm

Short Description

The LU4000 EX turning center is Okuma's latest evolution of 4-axis turning in the 10-15 inch chuck class.

Description

The LU4000 EX turning center is Okuma's latest evolution of 4-axis turning in the 10-15 inch chuck class. Two tools at work simultaneously provide process flexibility as well as high removal rates. The large work ranges of the upper (V12) and lower (V8) turrets mean less interference and more flexibility. The LU4000 EX has a 45-degree box bed with all box way construction, which provides optimum support for the carriage and cross slide. The three-point bearing support for the spindle means stability and long life for this very accurate spindle. The LU4000 EX is equipped with Okuma's OSP P300 control. The one-screen "easy operation" feature on this control system, combined with the open architecture design make it suitable for operators of all levels.

[MORE INFORMATION](#)

Specification

MODEL	UNIT	SIMUL TURN LU3000EX
Max Work Length	mm	350 (no tailstock)/600
Max Turning Dia	? mm	410 (340 for M Spec)
Spindle Speed	min-1	45~5000 (42~4200)
Turret Milling	min-1	45~6000
Main Motor	kW	22/15 (30mm/cont)
Milling Motor	kW	PREX 7.1/4.1 (25mm/cont)
Floor Space	mm	2,950x2,176
Spec		M/MY/2M

T Turning only

M Multitasking specs (M-tool)

W Sub-spindle specs (W-axis)

MY Multitasking + Y-axis specs

MYW Multitasking + Y-axis + Sub-spindle specs (W-axis)

2M Multitasking (upper/lower turrets)

Product Gallery

